



Giant Band

BAND-IT Giant Band is tough where tough counts. Giant Band produces the strongest band clamp in the industry. It is used primarily in the utility market and telecommunications. Giant Band can be formed into a single or double wrapped clamp configuration.

- The thickest BAND-IT band
- 201 Stainless Steel in a shiny finish, offers good resistance to oxidation and many moderate corrosive agents
- Used with BAND-IT G40269 tool and G44199 Giant Buckle (below)

Product	Material	Width		Thickness		Average Breaking Strength (Lbs)	Package Quantity	Weight		Use with Buckle Type
		In.	(mm)	In.	(mm)			Lbs.	Kg	Giant Ear-Lokt
G43099	201 SS	3/4	19.1	0.044	1.00	3300	100' Roll	11.6	5.4	G44099
G43199	201 SS	1	25.4	0.044	1.00	4400	100' Roll	13.7	6.4	G44199
G43299	201 SS	1 1/4	31.8	0.044	1.00	5500	100' Roll	17.2	8.0	G44299

Notes Galvanized Carbon Steel is also available

Giant Ear-Lokt Buckle

- 201 Stainless Steel offers good resistance to oxidation and many moderate corrosive agents
- Provides maximum strength
- Giant Style Buckle for use with G43099 3/4" Giant Band (above)
- Installed with the BAND-IT C00369 or G40269 Tools
- Ear-Lokt Style Buckle for heavy duty applications, can hold a single or double wrapped band configuration

Product	Material	Width		Package Quantity	Weight	
		In.	(mm)		Lbs.	Kg
G44099	201 Stainless Steel	3/4	19.1	25/Box	1.8	0.8
G44199	201 Stainless Steel	1	25.4	25/Box	2.4	1.1
G44299	201 Stainless Steel	1 1/4	31.8	25/Box	3.2	1.4

Application Tools



[G40269 Giant Tool](#)



[C00369 Heavy Duty BAND-IT® Tool*](#)

Notes

*Heavy Duty BAND-IT® Tool can be used with 3/4" Giant Band maximum