

Tie-Lok Ties

- Low Profile, Small head
- No slip back - Dual lock
- Minimum Loop Tensile Strength:-
 - Mini Tie-Lok - 100 Lbs (445N)
 - Tie-Lok - 200 Lbs (890N)
 - Ultra-Lok - 400Lbs (1776N)

Smooth I.D. Tie-Lok Ties Thickness .015" (.38mm) Pkg. Qty. 100

Stainless Steel Band width 0.25" (6.35mm)

| 304SS Cat. No. | 316SS Cat.No. | Max. Bundle Dia. | | Length | | Weight | |
|-------------------|------------------|------------------|-----|--------|-----|--------|------|
| | | In. | mm | In. | mm | Lbs. | Kg. |
| AS211 | AS411 | 2 | 51 | 10.0 | 254 | 1.2 | 0.54 |
| AS212 | AS412 | 4 | 101 | 16.5 | 419 | 1.8 | 0.86 |
| AS213 | AS413 | 6 | 152 | 22.5 | 572 | 2.6 | 1.17 |
| AS214 | AS414 | 8 | 203 | 29.0 | 737 | 3.3 | 1.50 |
| AS215 | AS415 | 10 | 254 | 35.0 | 889 | 3.9 | 1.79 |

0.38" (9.53 mm) wide version available on special order. Contact our Sales Desk.

Smooth I.D. Mini Tie-Lok Ties Thickness .015" (.38mm) Pkg. Qty. 100

Band width 0.177" (4.5mm)

| 304SS Cat. No. | 316SS Cat.No. | Max. Bundle Dia. | | Length | | Weight | |
|-------------------|------------------|------------------|-----|--------|-----|--------|------|
| | | In. | mm | In. | mm | Lbs. | Kg. |
| AS221 | AS421 | 1 | 25 | 6.5 | 165 | 0.7 | 0.30 |
| AS222 | AS422 | 2 | 51 | 10.0 | 254 | 0.9 | 0.40 |
| AS223 | AS423 | 4 | 102 | 16.0 | 406 | 1.4 | 0.61 |
| AS224 | AS424 | 6 | 152 | 22.5 | 572 | 1.9 | 0.84 |
| AS225 | AS425 | 8 | 203 | 29.0 | 737 | 2.4 | 1.06 |

Smooth I.D. Ultra-Lok Ties

Pkg. Qty. 100

Austenitic Stainless Steel Band Width 0.25" (6.35mm)

| Cat. No. | Max. Bundle Dia. | | Length | | Weight | |
|----------|------------------|-------|--------|-----|--------|------|
| | In. | mm | In. | mm | Lbs. | Kg. |
| AU202 | 1.5 | 38.1 | 8.0 | 203 | 1.0 | 0.45 |
| AU203 | 2.5 | 63.5 | 10.0 | 254 | 1.2 | 0.54 |
| AU204 | 3.0 | 76.2 | 12.0 | 305 | 1.4 | 0.64 |
| AU205 | 3.8 | 96.5 | 14.0 | 356 | 1.6 | 0.74 |
| AU206 | 4.5 | 114.3 | 16.0 | 406 | 1.9 | 0.86 |
| AU207 | 5.4 | 137.2 | 19.0 | 483 | 2.2 | 1.00 |
| AU208 | 7.0 | 177.8 | 24.0 | 610 | 2.7 | 1.22 |
| AU209 | 8.5 | 215.9 | 29.0 | 737 | 3.2 | 1.46 |
| AU215 | 10.5 | 266.7 | 35.0 | 889 | 3.9 | 1.75 |

Smooth I.D. Universal Clamps Pkg. Qty. 100

Austenitic Stainless Steel

Thickness .015" (.38mm) Width 0.25" (6.35mm)

| Cat. No. | Maximum Bundle Dia. | | Weight | |
|----------|---------------------|-----|--------|------|
| | In. | mm | Lbs. | Kgs. |
| JU242 | 1.0 | 25 | 1.2 | 0.54 |
| JU252 | 1.5 | 38 | 1.4 | 0.64 |
| JU253 | 2.0 | 51 | 1.7 | 0.77 |
| JU254 | 2.5 | 64 | 1.9 | 0.86 |
| JU256 | 3.0 | 75 | 2.2 | 1.00 |
| JU257 | 3.5 | 89 | 2.4 | 1.09 |
| JU258 | 4.0 | 102 | 2.6 | 1.18 |
| JU259 | 4.5 | 114 | 2.7 | 1.23 |



Pneumatic Tools IT1000 or IT3000

Pneumatic Tools

| Cat. No. | Description | Weight | |
|----------|---|--------|------|
| | | Lbs. | Kgs. |
| IT1000 | Pneumatic Tool for all 1/4" (6.35mm) Tie-Lok and Universal Bands / Clamps. | 10.4 | 4.70 |
| IT0750 | Pneumatic Tool for all 0.177" (4.5mm) Mini Tie-Lok Ties. | 10.4 | 4.70 |
| IT3000 | Pneumatic Tool for all 1/4" (6.35mm) Ultra-Lok and Tie-Lok Bands / Clamps. | 10.4 | 4.70 |
| IT6000 | Pneumatic Tool for all 3/8" (9.5mm) Tie-Lok Ties. | 10.4 | 4.70 |
| A370 | Bench Mounting and Foot Control Kit. | 1.4 | 0.63 |
| A320 | Pneumatic Tool Locator allows installation of clamp a constant distance from reference surface. | 0.4 | 0.20 |



IT1000

A920



IT0750

A910



IT3000

A940

Hand Tools

| Cat. No. | Description | Weight | |
|----------|---|--------|------|
| | | Lbs. | Kg. |
| A920 | Tie-Lok II Tool for Tie-Lok and Universal Clamps | 0.94 | 0.43 |
| A910 | Mini Tie-Lok Tool for Mini Tie-Lok Ties | 0.94 | 0.43 |
| A940 | Ultra-Lok Tool for Ultra-Lok Ties, Tie-Lok Ties, Universal Clamps | 0.94 | 0.43 |



IT1000
IT0750,
IT3000,
IT6000