

# Regulators

## Models 40, 41, and 42 Precision Pressure Regulators

### Introduction

#### Features & Benefits

- ▶ Multi-stage, low-droop precision regulators maintain constant output over wide changes in flow and supply pressure
- ▶ Epoxy powder coat paint delivers improved corrosion resistance
- ▶ Wide selection of regulated pressures [1" to 450 psi] affords application versatility
- ▶ Patented Nullmatic pressure regulation system provides reliable maintenance-free operation

#### Description

The Models 40, 41, and 42 Precision Pressure Regulators control air pressures in applications where precise and dependable regulation is required, such as pneumatic instrument circuits, test stands, production checking fixtures, and industrial air gages. As such, they are suitable for dead-end service, and flows up to a maximum of 110 scfm.

A unique, two-stage piloted design provides outstanding accuracy. Rugged construction—with no links, levers, pivots, or other friction-producing members—ensures reliable, maintenance-free operation. These features allow a regulator to maintain constant output pressure, regardless of even the widest changes in flow or supply pressures. In fact, a regulator using a Model 40, 41, or 42 is practically a self-contained pressure controller operating its supply-plunger valve via a built-in, high-gain pneumatic amplifier.

A fine-turn, precision screw is used to manually load the range spring, which sets the regulated pressure. When the adjusting knob is turned clockwise, the increased spring force is exerted on the top diaphragm assembly, decreasing the nozzle clearance and increasing the pilot pressure. Because the source for pilot pressure is supply air flowing to the pilot pressure chamber through the restriction screw, the increased pilot pressure forces the exhaust diaphragm assembly downward. This action closes the exhaust port, and contacts and moves the valve plunger, which opens the supply port. This increases the regulated output, which also feeds back to the top diaphragm assembly. The regulator locks-up or throttles at the new output value when the feedback force of the top diaphragm assembly equals the range spring force.

A safety release valve is incorporated in the top diaphragm assembly of several models. It operates if the regulated pressure increases 3 tnU psig more than the set pressure and exhausts air through the atmospheric vent in the top housing. Overpressure causes the diaphragm to move upward, which opens the safety release valve.



#### Specifications

##### Resolution Adjustment

Better than 0.03% of regulated output

##### Supply Pressure

Maximum & recommended pressures are listed on page 220

Minimum: 5 psig above regulated output

##### Supply Pressure Effect

Nominal ratio of change in regulated pressure for a change in supply

1:150 for Model 40 and 42

1:100 for Model 41

##### Ambient Temperature Limits

-40 to 180°F (-40 to 80°C)

##### Ambient Temperature Effect

Approximately 1% of set pressure with standard range spring; and approximately 0.1% with Isothermal spring for 50°F (27°C) temperature change

##### Knob Adjustment

Model 40 & 42: Nominal 10% of full range for one complete turn

Model 41: Nominal 15% of full range for one complete turn

##### Droop Effect

See Graph 1

##### Maximum Air Flow

See Graph 2

# Regulators

## Models 40, 41, and 42 Precision Pressure Regulators

### Technical data

#### Air Consumption

See Graph 3

#### Drift Effect

See Graph 4

#### Exhaust-Flow Rate (at 25-psig setting)

Pressure rise of 0.25 psig will result from flow of:

Model 40: 1.5 scfm

Model 41: 2.4 scfm

Model 42: 1.7 scfm

#### Maximum Flow Capacity

See Graph on page 219

#### Standard Mounting

In-line pipe or flush panel up to 1/4" thick (bushing for 3/4" thick panel is optional)

Connections: (supply and outlet)

Model 40: 1/4" NPT

Model 41: 1/8" NPT

Model 42: 1/2" NPT

**Materials of Construction** (and materials in contact with regulated media)

Brass, stainless steel, Neoprene, aluminum, and zinc

#### Accessories

- ▶ P/N 2932-19 - Mounting Bracket for surface mounting (Model 40 and Model 42)
- ▶ P/N 10963-73 - Mounting Bracket for surface mounting (Model 41)
- ▶ P/N 3603-22 - Locknut

#### Options

##### ▶ Air Loading

Provision for supplementary air loading (100 psig max) in addition to spring loading

Model 40, 42: 1/4" NPT

Model 41: 1/8" NPT

Model 40-2: Not available

Add [A] into the model number.

Example: 40A15

##### ▶ Tapped Exhaust

Provision for piping exhaust flow away from the regulator

Model 40, 42: 1/8" NPT

Model 41: Not available

Add [E] into the model number.

Example: 40E15

##### ▶ Isothermal Range Spring

Reduces ambient temperature effect from approximately 1% of set pressure to approximately 0.1% for a 50°F

[27°C] temperature range

Model 40: 15, 30, 50, & 100 psig ranges

Model 41: Not available

Model 42: 30, 50, & 100 psig ranges

Add (M9) to the Moore 40 number.

Add (M26) to the Moore 42 model number.

Example: 40-15M9, 42-30M26

##### ▶ Deletion of Safety Release Valve (SRV)

The SRV increases exhaust flow capacity when the regulator must exhaust large flows. Deletion of the SRV will improve drift characteristics (see Graph 4). The SRV is not

available with the Moore 41. It is standard with:

Model 40: 2, 7, 15, 30, 50 & H50 pressure ranges

Model 42: 15, 30, 50, H30, & H50 pressure ranges

To delete the SRV, add an [X] into the model number.

Example: 40X15

##### ▶ Slotted Adjusting Screw

Available for all models. This option provides for screw-driver adjustment of the regulator and includes a locknut.

Model 40: Add (M3) after the model number

Model 41: Add (M3) after the model number

Model 41: Add (M20) after the model number

Example: 40-15(M3)

##### ▶ Locknut with Longer Adjusting Screw

Available for all models. This option prevents inadvertent regulator adjustment.

Model 40: Add (M13) after the model number.

(Note: The Model 40-2 is standard with the lock nut.)

Model 41: Add (M5) after the model number or order

accessory P/N 3603-22.

Model 42: Add (M3) after the model number

Example: 40-15(M3)

##### ▶ Bushings for mounting on panels up to 3/4" thick

(Standard maximum is 1/4" thick).


Model 40: Add (M41) after the model number

Model 41: Not available

Model 42: Add (M14) after the model number

Example: 40-15(M41)

7




# Regulators

## Models 40, 41, and 42 Precision Pressure Regulators

Technical data

Graph 1 Droop Effect



**Test Procedure:** Each 30-psig-range regulator was adjusted to 25 psig with 100 psig supply and no flow. Flow was increased to maximum capacity. All regulated pressure readings were taken at gauge connection in the body of the regulator.


**Note:** For performance curves on Model 40-2 and 40-7, request drawing # 1709-4 and 2155-72, respectively.

# Regulators


## Models 40, 41, and 42 Precision Pressure Regulators

### Technical data


**Graph 2 Maximum Air Flow, SCFM Delivered**



**Graph 3 Air Consumption**



**Graph 4 Drift Effect**



Test Procedure: Regulators were set at 20 psig output with 100 psig air supply. Supply was turned off for one week, after which supply was turned on at time 0.

The Nullmatic regulator bleeds only the amount of air that passes through the pilot nozzle when there is no demand for output flow. The exhaust port starts to close as soon as the flow of regulated air is increased to the output, and it closes completely before the pilot-plunger valve opens. Full pilot flow is then delivered to the output.

# Regulators

## Models 40, 41, and 42 Precision Pressure Regulators

### Technical data

#### Model Selection

Model No.	Range psig <sup>3</sup>	Supply Pressure psig				Gauge (Opt.) Dia. Inches
		Recommended	Maximum	Pipe Mtg.	Panel Mtg.	Standard Modifications
40-2 <sup>1</sup>	(1-50"H <sub>2</sub> O)	5-10	25	3-1/2	3-1/2	E & X
40-7	(6-200"H <sub>2</sub> O)	50	100	3-1/2	3-1/2	A, E & X
40-15	0.5-15	75	150	3-1/2	3-1/2	A, E & X
40-30	1-30	120	150	3-1/2	3-1/2	A, E & X
40-50	1-50	120	150	3-1/2 <sup>4</sup>	3-1/2 <sup>4</sup>	H, A, E & X
40-100	1.5-100	150	500	3-1/2	3-1/2	H, A & E
40-200	3-200	250	500	3-1/2	3-1/2	A & E
40-300	7-300	350	500	3-1/2	3-1/2	A & E
40-450	15-450	500	500	3-1/2	3-1/2	A & E
41-15	0.5-15	75	150	2 <sup>5</sup>	3-1/2	A
41N15 <sup>2</sup>	0.5-15	75	150	2 <sup>5</sup>	3-1/2	
41-30	1-30	120	150	2	3-1/2	A
41-50	1-50	120	150	2 <sup>4</sup>	3-1/2 <sup>4</sup>	A
41-100	1.5-100	150	250	2	3-1/2	A
41-2550	25-50	120	150	2	3-1/2	
42-15	0.5-15	75	150	3-1/2	3-1/2	A, E & X
42-30	1-30	120	150	3-1/2	3-1/2	H, A, E & X
42-50	1-50	120	150	3-1/2 <sup>4</sup>	3-1/2 <sup>4</sup>	H, A, E & X
42-100	1.5-100	150	500	3-1/2	3-1/2	H, A & E
42-200	3-200	250	500	3-1/2	3-1/2	A & E

*Standard Modifications*

H - High flow capacity.

A - With pressure-tight top housing, containing 1/4" NPT connection for supplementary air loading.

E - With 1/8" NPT connection to collect exhaust when used with gases other than air.

X - Without safety release.

1) Includes locknut on adjusting stem (optional for all other models).

2) For use with Model 65 Square-Root Extractor to maintain minimum 3 psig output.

3) At recommended supply pressure.

4) With 0-60 psig dial range.

5) For pipe-mounting, 2" dia. gauge (0-30 psig) is available.

# Regulators

## Models 40, 41, and 42 Precision Pressure Regulators

### Dimensional drawings

#### Mounting Dimensions

